



MATERIAL SAFETY DATA SHEET

IDENTIFICATION

LABEL NAME: YLANG YLANG EXTRA
CODE NUMBER: 50-6295-02-01
BOTANICAL NAME CANANGA ODORATA

CAS NUMBER: 8006-81-3
FEMA NUMBER: 3119
FDA NUMBER: 182.20

PHYSICAL DATA

APPEARANCE: PALE YELLOW LIQUID

SPECIFIC

0.941

REFRACTIVE

1.510

GRAVITY:

INDEX:

MELTING POINT: N/F

BOILING POINT:

VAPOR

N/F

VAPOR DENSITY: N/F

PRESSURE:

EVAPORATION

N/F RATE:

SOLUBILITY IN

INSOLUBLE

WATER:

FIRE, EXPLOSION AND REACTIVITY

FLASHPOINT: 87 DEGREES C. CLOSED CUP

STABILITY: STABLE UNDER NORMAL CONDITIONS

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM

HEALTH: 0

FLAMMABILITY: 0

REACTIVITY: 0

PERSONAL PROTECTION: 0

4 = EXTREME 3 = HIGH 2 = MODERATE 1 = SLIGHT 0 = NO SIGNIFICANT HAZARD

EXTINGUISHING MEDIA

☐ WATER/FOG ☒ CARBON DIOXIDE ☒ FOAM ☒ DRY CHEMICAL

SPECIAL FIRE FIGHTING PROCEDURE/UNUSUAL FIRE AND EXPLOSION HAZARDS:

NONE KNOWN. USE SELF CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING

HAZARDOUS COMBUSTION/DECOMPOSITION PRODUCT:

BURNING PRODUCES CARBON MONOXIDE AND CARBON DIOXIDE

HAZARDOUS POLYMERIZATION PROCUCT:

WILL NOT OCCUR

CONDITIONS AND MATERIALS TO AVOID:

ELEVATED TEMPERATURES ABOVE 60 DEGREES CENTIGRADE, AVOID
STRONG OXIDIZING AGENTS

PROTECTION INFORMATION:

RESPIRATORY PROTECTION:	NOT USUALLY NECESSARY, BUT APPROVED RESPIRATOR CAN BE USED IF DESIRED
EYE PROTECTION:	USE SPLASH GOGGLES
SKIN PROTECTION:	USE CHEMICAL RESISTANT GLOVES
VENTILATION:	LOCALIZED EXHAUST CAN BE USED TO REMOVE VAPORS
OTHER:	EYE WASH STATION AND SAFETY SHOWER RECOMMENDED IN AREA

OCCUPATIONAL EXPOSURE LIMITS

THRESHOLD LIMIT VALUE (TLV):	N/F
EFFECTS OF OVEREXPOSURE:	REDNESS OF SKIN AND/OR EYES
OSHA PERMISSIBLE EXPOSURE (PEL):	N/F LIMIT

HAS SUBSTANCE BEEN LISTED AS A ☐ YES ☒ NO
CARCINOGEN: NO

HEALTH HAZARD INFORMATION

- MAY BE IRRITATING TO SKIN AND EYES
- VAPOR MAY BE IRRITATING TO THROAT AND LUNGS
- BREATHING HIGH CONCENTRATIONS OF VAPOR MAY CAUSE ANESTHETIC EFFECTS
- REPEATED CONTACT MAY CAUSE ALLERGIC DERMATITIS

EMERGENCY AND FIRST AID PROCEDURES

INHALATION:	REMOVE TO FRESH AIR
EYE CONTACT:	FLUSH WATER FOR 15 MINUTES
SKIN CONTACT:	REMOVE CONTAMINATED CLOTHING AND WASH WITH SOAP AND WATER
INGESTION:	DRINK WATER OR MILK TO DILUTE, CONTACT POISON CONTROL

SPILLS LEAKS AND DISPOSAL PROCEDURE

IF MATERIAL SHOULD BE SPILLED OR RELEASED: ELIMINATE FLAMES AND SOURCES OF IGNITION, WIPE UP SMALL SPILLS WITH A CLOTH, LARGER SPILLS USE PORUS ABSORBANT

WASTE DISPOSAL METHODS: FOLLOW STATE, LOCAL AND FEDERAL LAWS

HANDLING AND SHIPPING PROCEDURES

HANDLE ACCORDING TO GOOD SAFETY PROCEDURES AVOIDING UNNECESSARY EXPOSURE. STORE IN FULL CLOSED CONTAINERS AWAY FROM HEAT, LIGHT AND SOURCES OF IGNITION. STORE IN COOL AREA.

THE INFORMATION CONTAINED IN THIS MATERIAL SAFETY DATA SHEET WAS OBTAINED FROM CURRENT AND RELIABLE SOURCES. THIS DATA IS

SUPPLIED WITHOUT WARRANTY, EXPRESSED OR IMPLIED, REGARDING ITS CORRECTNESS OR ACCURACY. IT IS THE USER'S RESPONSIBILITY TO DETERMINE SAFE CONDITIONS FOR USE OF THIS PRODUCT AND TO ASSUME LIABILITY FOR LOSS, INJURY, DAMAGE OR EXPENSE RESULTING FROM IMPROPER USE OF THIS PRODUCT.

Danger PHRASES / CODES:	R22 R65
RISK PHRASES / CODES:	R22 R65
SAFETY PHRASES / CODES:	S62